

FEATURES

- Easy to mount when space is limited. The reader measures only 37 mm in width.
- Support for MIFARE, MIFARE Plus, DESFire
- Ingress protection IP54
- Illuminated keyboard
- Door environment status indicated by red and green LFDs
- Low power consumption
- Full support for PACOM 8602 Multi Interface Module



PACOM 8704 Slim is an optimal card reader which, due to its "slimmed" design, opens up the possibility for secure passage solutions at facilities with limited space and narrow environments. The illuminated membrane keyboard has a built-in self-adjustment of the brightness level and is automatically illuminated when needed, making the reader a suitable alternative even in environments with limited lighting.

The PACOM 8704 Slim Reader with its illuminated keyboard is easy to mount in limited spaces and visible in poorly lit environments.

TECHNICAL SPECIFICATION

ELECTRICAL	
Input Voltage	24VDC ±- 15%
Current Consumption	Normally 50mA Maximum 65mA
ENVIRONMENTAL	
Enclosure Class	IP54
Operating Temperature	-25 to 50°C (-13 to 122°F)
Maximum Humidity	69% ± 5% relative humdity
PHYSICAL	
Reader Color	Black
Dimensions	37 x 135 x 30mm (1.5 x 5.3 x 1.2")
Weight	130g (4.6oz)
Reading Distance	30 to 40mm (1.2 to 1.6")
COMMUNICATION	
Port	1 x RS485
Addressing	1 to 4
Frequency Carrrier / Standards	13,56 MHz. ISO14443 tipo A
SECURITY	
Tamper Switch	Yes
MISCELLANEOUS	
Optical Indication	2 LEDs - read and green
Acoustic Indication	Built-in buzzer
Card Technologies	MIFARE MIFARE Plus DESFire

ORDERING INFORMATION

PART NUMBER	TYPE CODE	DESCRIPTION	
300 048 012	8704R-001	PACOM 8704 Slim Reader with RS485 output and keypad	
300 048 014	8704R-MP	PACOM 8704 Slim Reader Mounting Plate Minimum order quantity 10 units	